

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Manufacturer's Name: N-TRON Corporation  
 Manufacturer's Address: 820 S. University Blvd., Ste 4E  
 Mobile, Alabama 36609 USA



USA: TEL +1 (251) 342-2164      China: TEL +86 0.21.6113.3688  
 United Kingdom: TEL +44 (0) 1928.577257      India: TEL +91-9844-876540  
 Switzerland: TEL +41 41.740.6636      Singapore: TEL +65-8188-6821

Hereby, N-TRON Corporation declares that these industrial Ethernet devices are in compliance with the essential requirements and other relevant provisions of Directives 1999/5/EC and 2004/108/EC.

<u>Listing of conforming devices:</u>			
102MC-XX	304TX-N	317FX-N-SC-S	509FX-A-XX-S
102MCE-XX-YY	306TX	317FX-N-ST-S	509FXE-XX-YY
104TX	306TX-N	317FXE-N-SC-XX	509FXE-N-XX-YY
105TX, 105TX-SL	305FX-XX	317FXE-N-ST-XX	509FXE-A-XX-YY
105FX-XX	305FX-N-XX	508TX	516TX
105FXE-XX-YY	305FXE-XX-YY	508TX-N	516TX-N
106FX2-XX	305FXE-N-XX-YY	508TX-A	516TX-A
106FXE2-XX-YY	306FXE2-N-XX-YY	508FX2-XX	517FX-XX
108TX	306FX2-N-XX	508FX2-XX-S	517FX-XX-S
100-POE4	306FXE2-XX-YY	508FX2-N-XX	517FX-N-XX
105TX-POE	306FX2-XX	508FX2-N-XX-S	517FX-N-XX-S
105FX-POE	308TX	508FX2-A-XX	517FX-A-XX
105FX-XX-POE	308TX-N	508FX2-A-XX-S	517FX-A-XX-S
105M12	308FX2-N-SC/ST	508FXE2-XX-YY	517FXE-XX-YY
108M12	308FXE-N-SC-XX	508FXE2-N-XX-YY	517FXE-N-XX-YY
302MC-XX	308FXE-N-ST-XX	508FXE2-A-XX-YY	517FXE-A-XX-YY
302MC-N-XX	309FX-N-SC/ST	509FX-XX	524TX
302MCE-XX-YY	309FXE-N-SC-XX	509FX-XX-S	524TX-N
302MCE-N-XX-YY	309FXE-N-ST-XX	509FX-N-XX	524TX-A
304TX	316TX/316TX-N	509FX-N-XX-S	526FX2-XX
		509FX-A-XX	526FX2-XX-S
			526FX2-N-XX
			526FX2-N-XX-S
			526FXE2-XX-YY
			526FXE2-N-XX-YY
			526FXE2-A-XX-YY
			708TX
			708FX2-XX
			708FXE2-XX-YY
			708M12
			9000BP
			9000CPU
			9002CPU-SX
			9002CPU-LX-YY
			9002FX-XX
			9002FXE-XX-YY
			9004FX-XX
			9004FXE-XX-YY
			9006TX
			1002MC
			1003GX2
			1005TX

Operating Temperature -40°C to 85°C (except where noted); Operating voltage 10-30 VDC and 46-49 VDC depending on device; Where -N = N-View; -A = Advanced Management; S = Standard Temperature -20°C to 70°C; XX = SC or ST Style Fiber Connector; YY = 15km, 40km, or 80km range except for 9000 series where YY = 5km, 10km, 15km, 30km, 40km, 70km or 80km.

Standards of conformance: The products herewith comply with the requirements of ABS-Type Approvals (Steel Vessel Rules: International Association of Classification Societies (IACS) E10: Rev. 4, May 2004)

IEC60068-2-1	IEC61000-4-5	IEC61000-4-3	IEC60533
IEC60068-2-30	IEC60068-2-2	IEC61000-4-6	IEC61000-4-4
IEC61000-4-2	IEC60092-504	IEC60068-2-6	

Mr. Jerry Simmons  
 Regulatory Manager

Notified Body:  
 Mariners Systems (UK) Ltd  
 Unit 13/14, Enterprise City  
 Meadowfield Avenue  
 Spennymoor  
 Co. Durham DL16 6JF UK  
Test Report: TL1212

Notified Body:  
 ABS Americas  
 16855 Northchase Drive  
 Houston, Texas 77060  
<http://www.eagle.org>  
Test Reports: 06-HS176465(A/B/C)/1-PDA  
 and 08-LD412000/1-PDA

